

Datenblatt

Installationsschutz




Montageart: Hutschiene 35mm
 Farbe: hellgrau
 Schutzart: IP20
 Umgebungstemperatur: -5°C bis +60°C




Art.Nr.	7010.00020.0198	25A 2S	STM-25-20	EAN	5903669487296
Art.Nr.	7010.00020.0298	25A 4S	STM-25-40	EAN	5903669487364
Art.Nr.	7010.00022.0398	40A 4S	STM-40-40	EAN	5903669487371
Art.Nr.	7010.00023.0198	63A 4S	STM-63-40	EAN	5903669487401

Technische Daten

	STM-25-20	STM-25-40	STM-40-40	STM-63-40
Betriebsspannung:	230V AC	400V AC	400V AC	400V AC
Steuerspannung:	230V AC	230V AC	230V AC	230V AC
Nennstrom:	25A	25A	40A	63A
Kontakte:	2x NO	4x NO	4x NO	4x NO
Isolationsspannung: U_i	500V AC	500V AC	500V AC	500V AC
Stoßspannung: U_{imp}	0,5kV	0,5kV	0,5kV	0,5kV
Anschlussquerschnitt:	max. 4mm ²	max. 4mm ²	max. 16mm ²	max. 16mm ²
Lebensdauer:	100.000x	100.000x	100.000x	100.000x
Eigenverbrauch:	>1W	>1W	>1W	>1W
Abmessungen: lxbxh	68x18x81mm	68x36x81mm	68x54x85mm	68x54x85mm



STM-25-20



STM-25-40
 STM-40-40
 STM-63-40